



# KAMFLEX, LLC

## APPLICATION DATA SHEET



DATE: \_\_\_\_\_

CUSTOMER: \_\_\_\_\_

CONTACT: \_\_\_\_\_

PHONE: \_\_\_\_\_ Email \_\_\_\_\_

PRODUCT DESCRIPTION: \_\_\_\_\_

Transfer Rate (PPH): \_\_\_\_\_ Bulk Density (P/CF): \_\_\_\_\_

Product Temperature: \_\_\_\_\_ Moisture Content: \_\_\_\_\_

Method of Feed To Conveyor: \_\_\_\_\_

Conveyor Discharge (Into/Onto): \_\_\_\_\_

### CONVEYOR INFORMATION:

Length: \_\_\_\_\_ Width: \_\_\_\_\_ Speed (FPM): \_\_\_\_\_

Plant Power \_\_\_\_\_ Belt Material (Fabric, Molded Plastic, S.S.) \_\_\_\_\_

Constant Speed \_\_\_\_\_ Variable Speed \_\_\_\_\_ 90VDC \_\_\_\_\_ VFD \_\_\_\_\_

Infeed Height (TOB) \_\_\_\_\_

Discharge Height (TOB) \_\_\_\_\_

Max. Weight on Belt (Lbs.) \_\_\_\_\_ Flat Bed \_\_\_\_\_ Troughed Bed \_\_\_\_\_

S.S. Laced Splice \_\_\_\_\_ Spliced "Endless" \_\_\_\_\_

Cleat Height \_\_\_\_\_ On Centers \_\_\_\_\_

Corrugated Sidewall Height \_\_\_\_\_ Drive Location (Right / Left Side) \_\_\_\_\_

Supports By Kamflex \_\_\_\_\_ Supports By Others \_\_\_\_\_

### OPERATING ENVIRONMENT:

Temperature \_\_\_\_\_ Humid \_\_\_\_\_ Dry \_\_\_\_\_ Dusty \_\_\_\_\_

Controlled \_\_\_\_\_ Washdown (Y/N) \_\_\_\_\_ Hours / Day Usage \_\_\_\_\_

### OPTIONS:

Side Rail Height: \_\_\_\_\_ Discharge Slide (Open): \_\_\_\_\_

Discharge Chute (Enclosed): \_\_\_\_\_ Leveling Feet (+/- 2" Std.): \_\_\_\_\_

Casters (+/- 1.5" Std.): \_\_\_\_\_ Infeed Hopper \_\_\_\_\_

S.S. Top Covers: \_\_\_\_\_ LEXAN Top Covers: \_\_\_\_\_

S.S. Drip Pans \_\_\_\_\_ LEXAN Drip Pans: \_\_\_\_\_

Workshelves (Size) \_\_\_\_\_ UHMW Cutting Boards (Yes/No) \_\_\_\_\_

SPECIAL NOTES: \_\_\_\_\_

\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

SKETCH: Separate Page